

fluid RINSEABLE PRIMER APPLIED ROOFING™ CONCENTRATE

PRODUCT DESCRIPTION

Mixing required – See mixing instructions. The Rinseable Primer™ is a bio-degradable surface cleaner and degreaser. It can be used to clean various types of roofing substrates. The cleaner removes the heavy accumulation of hard-to-remove dirt, oil, and grease without using solvents. When old surfaces are cleaned properly, it will eliminate the need for solvent wiping, sanding, and grit sweeping the substrate. This will not damage grass or vegetation near the building.

- Promotes adhesion.
- Powerful degreaser.
- Solvent free.
- Biodegradable.
- Low odor.
- Easy to apply.
- Contains no phosphates, halogens, or alkali hydroxides.
- Formulated without lead or mercury-containing materials.
- Dramatically improves adhesion of aged, painted surfaces.

RECOMMENDED USES

Recommended for cleaning roofing substrates such as:

- EPDM
- TPO
- PVC
- GALVANIZED METAL
- CONCRETE
- PREVIOUSLY PAINTED SURFACES

NOT recommended for cleaning asphalt-based surfaces.

Rinseable Primer Concentrate™ is ideal for cleaning intact painted surfaces in preparation for repainting. It is also useful in cleaning rusted steel, galvanized metal, and masonry surfaces. It is beneficial for cleaning dirty, greasy concrete floors, walls, machinery, and equipment in industrial and commercial environments.

SURFACE PREPARATION

All surfaces to receive the FAR® System must be power washed to remove dirt, loose rust, loose paint, chalk, and other debris that could prevent adhesion. The surface must be dry before coating.

APPLICATION CONDITIONS

Do not apply when rain is forecast or when temperatures are below 50°F (10°C).

APPLICATION TEMPERATURE: 50° F to 105° F (10° C to 40° C)

KEEP FROM FREEZING

PACKAGING INFORMATION

Container: 18 oz bottles (0.53 L).

Packaging: Box of (4) 18 oz bottles. Shipping Weight: 5.5 lbs.

Packaging: Box of (12) 18 oz bottles. Shipping Weight: 16.5 lbs.



RINSEABLE PRIMER CONCENTRATE

APPLICATION PROCEDURES

Clean a small area to ensure compatibility with the substrate. If the surface is hot, wet the surface before applying the Rinseable Primer™. It is recommended that this be applied with a low-pressure hand pump sprayer. Allow the cleaner to remain for five to ten minutes, but do not allow the surface to dry. Rinse with a minimum 1500 psi power washer. All of the residues must be removed, so thorough rinsing is very important. If the surface is extremely dirty, moderate scrubbing will aid in the performance and speed of cleaning. When completely removed, the surface will no longer foam when rinsed. Rinseable Primer™ must not be allowed to dry on the surface. Do not apply under freezing conditions. Allow the surface to dry thoroughly before applying any FAR System™ products. Do not apply to glass surfaces, metallic automobile finishes, aluminum surfaces that will remain unpainted, or strong alkali-sensitive painted surfaces. May dull glossy surfaces.

WARRANTY

Seller and manufacturer's only obligation shall be to replace such quantity of the product proved to be defective. Neither seller nor manufacturer shall be liable for any injury, loss, or damage, direct or consequential, arising from the use or the inability to use the product for their intended use. The user assumes all risk and liability.

DISCLAIMER

The information and recommendations outlined in this product datasheet are based upon tests conducted by or on behalf of Fluid Applied Roofing, LLC. Such information and recommendations set forth herein are subject to change and pertain to the product offered at the time of the publication. Consult your Fluid Applied Roofing representative to obtain the most current Product Data information.

MIXING INSTRUCTIONS

Pour one 18 oz bottle of Rinseable Primer™ into a 5-gal pail and fill with water.

COVERAGE RATES

After following the mixing instructions, apply Rinseable Primer™ at .25 gals per square (400 SF/gal). Ensure that the entire surface is wet. The coverage rate per 8 oz bottle, once diluted per the Mixing Instructions, is 2,000 SF.

SAFETY PRECAUTIONS

This product is intended for use only by professional applicators in industrial situations in accordance with the advice given on this sheet, the Safety Data Sheet, and the container(s) and should not be used without reference to the Safety Data Sheet (SDS), which Fluid Applied Roofing, has provided to its customers. All work involving the application and use of this product should be performed in compliance with all relevant national, Health, Safety, and environmental standards and regulations. In the event welding or flame cutting is performed on metal coated with this product, dust, and fumes will be emitted, which will require the use of appropriate personal protective equipment and adequate local exhaust ventilation. If in doubt regarding the suitability of use of this product, consult Fluid Applied Roofing for further advice. Adequate protective equipment and clothing, such as rubber gloves and protective eyewear, are recommended.

STORAGE

Shelf Life - 24 months minimum at 25°C (77°F). Subject to re-inspection thereafter. Store in dry, shaded conditions away from sources of heat and ignition.

fluid RINSEABLE PRIMER APPLIED ROOFING™ CONCENTRATE

